



NOTES:-

PART TO BE FREE FROM BURRS & SHARP EDGES.

|              |     |     |                                                       |      |      |       |            |
|--------------|-----|-----|-------------------------------------------------------|------|------|-------|------------|
| ER17C0004669 | AF  |     | ER RELEASE                                            | MMP  | RPK  | SAB   | 24.01.2018 |
| ECN18P002841 | AE  |     | HOLE $\varnothing$ 20 CHANGED INTO SLOT 20X25         | MMP  | RPK  | SAB   | 29.12.2017 |
| ECN17P002152 | AD  |     | HOLE SIZE $\varnothing$ 20 mm WAS $\varnothing$ 18 mm | MMP  | RPK  | SAB   | 03.08.2017 |
| ECN17P001708 | AC  |     | L2 RELEASE                                            | SSP  | RPK  | SAB   | 21.03.17   |
| ECN16P000572 | AB  | --- | AS PER L1 FEEDBACK                                    | SPR  | RPK  | SAB   | 28.06.16   |
| ECN16P000570 | AA  | --- | AS PER L0 FEEDBACK                                    | SPR  | RPK  | SAB   | 26.08.15   |
| E.R.NO.      | LET | LOC | REVISIONS                                             | DSNF | CKR. | APPR. | DATE       |

| <SC> :SIGNIFICANT CHARACTERISTICS                                                                                             |      |                                            |              |    |                        |               |          |      |                           | ▽ :CRITICAL CHARACTERISTICS                                                                |          |  |       |                                 |                           |  |     |  |  |  |  |  |
|-------------------------------------------------------------------------------------------------------------------------------|------|--------------------------------------------|--------------|----|------------------------|---------------|----------|------|---------------------------|--------------------------------------------------------------------------------------------|----------|--|-------|---------------------------------|---------------------------|--|-----|--|--|--|--|--|
| BREAK SHARP CORNERS MAY BE EITHER A CHAMFER OR A RADIUS FROM 0.2 mm MIN. TO 1.0 mm MAX.                                       |      |                                            |              |    |                        |               |          |      |                           | MAHINDRA & MAHINDRA LIMITED<br>TRACTOR DIVISION<br>KANDIVLI (EAST), MUMBAI 400 101, INDIA. |          |  |       |                                 |                           |  |     |  |  |  |  |  |
| UNSPECIFIED TOLERANCES AS PER ISO-2768-1:1989                                                                                 |      |                                            |              |    |                        |               |          |      |                           | E.R. / PROC.REQ.NO :<br>ER17C0004669                                                       |          |  |       |                                 | PART NO. :<br>008005844C1 |  |     |  |  |  |  |  |
| DIMENSIONS                                                                                                                    |      |                                            |              |    |                        |               |          |      |                           | PART NAME :<br>REAR PLATE - MTG. BRKT.                                                     |          |  |       |                                 |                           |  |     |  |  |  |  |  |
| LINEAR<br>IN mm.                                                                                                              | OVER | 0.5                                        | 3            | 6  | 30                     | 120           | 400      | 1000 | 2000                      |                                                                                            |          |  |       |                                 |                           |  |     |  |  |  |  |  |
|                                                                                                                               | UPTO | 3                                          | 6            | 30 | 120                    | 400           | 1000     | 2000 | 4000                      |                                                                                            |          |  |       |                                 |                           |  |     |  |  |  |  |  |
| f FINE                                                                                                                        |      | (X.XXX)                                    | ± 0.05       |    | ± 0.05                 |               | ± 0.1    |      | ± 0.15                    |                                                                                            | ± 0.2    |  | ± 0.3 |                                 | ± 0.5                     |  | -   |  |  |  |  |  |
| m MEDIUM                                                                                                                      |      | (X.XX )                                    | ± 0.1        |    | ± 0.1                  |               | ± 0.2    |      | ± 0.3                     |                                                                                            | ± 0.5    |  | ± 0.8 |                                 | ± 1.2                     |  | ± 2 |  |  |  |  |  |
| c COARSE                                                                                                                      |      | (X.X )                                     | ± 0.2        |    | ± 0.3                  |               | ± 0.5    |      | ± 0.8                     |                                                                                            | ± 1.2    |  | ± 2   |                                 | ± 3                       |  | ± 4 |  |  |  |  |  |
| v VERY COARSE (X )                                                                                                            |      | -                                          | ± 0.5        |    | ± 1                    |               | ± 1.5    |      | ± 2.5                     |                                                                                            | ± 4      |  | ± 6   |                                 | ± 8                       |  |     |  |  |  |  |  |
| ANGULAR<br>IN deg.                                                                                                            |      | LENGTH OF SHORTER SIDE OF THE ANGLE IN mm. |              |    |                        |               |          |      |                           |                                                                                            |          |  |       |                                 |                           |  |     |  |  |  |  |  |
|                                                                                                                               |      | OVER                                       | -            |    | 10                     |               | 50       |      | 120                       |                                                                                            | 400      |  |       |                                 |                           |  |     |  |  |  |  |  |
|                                                                                                                               |      | UPTO                                       | 10           |    | 50                     |               | 120      |      | 400                       |                                                                                            | -        |  |       |                                 |                           |  |     |  |  |  |  |  |
| f FINE                                                                                                                        |      | (X.XXX)                                    | ± 1°         |    | ± 0° 30'               |               | ± 0° 20' |      | ± 0° 10'                  |                                                                                            | ± 0° 5'  |  |       |                                 |                           |  |     |  |  |  |  |  |
| m MEDIUM                                                                                                                      |      | (X.XX )                                    |              |    |                        |               |          |      |                           |                                                                                            |          |  |       |                                 |                           |  |     |  |  |  |  |  |
| c COARSE                                                                                                                      |      | (X.X )                                     | ± 1° 30'     |    | ± 1°                   |               | ± 0° 30' |      | ± 0° 15'                  |                                                                                            | ± 0° 10' |  |       |                                 |                           |  |     |  |  |  |  |  |
| v VERY COARSE (X )                                                                                                            |      | (X )                                       | ± 3°         |    | ± 2°                   |               | ± 1°     |      | ± 0° 30'                  |                                                                                            | ± 0° 20' |  |       |                                 |                           |  |     |  |  |  |  |  |
| PART OF THIS DRAWING / DOCUMENT SHOULD NOT BE REPRODUCED IN ANY FORM OR BY ANY MEANS WITHOUT WRITTEN PERMISSION OF M & M LTD. |      |                                            |              |    |                        |               |          |      |                           |                                                                                            |          |  |       |                                 |                           |  |     |  |  |  |  |  |
| COMPUTER GENERATED DRAWING                                                                                                    |      |                                            |              |    | DO NOT CHANGE MANUALLY |               |          |      |                           |                                                                                            |          |  |       |                                 |                           |  |     |  |  |  |  |  |
| IF IN DOUBT, ASK                                                                                                              |      |                                            | DO NOT SCALE |    |                        | DRG SIZE : A3 |          |      | ALL DIMENSIONS ARE IN mm. |                                                                                            |          |  |       | CHECK DRG WITH LATEST CHANGE No |                           |  |     |  |  |  |  |  |